

*Northeast Sled Services LLC*  
*2023 4x4 Diesel Workstock / 8750lbs*

**General Diesel truck specifications explained:** This is a **STREET LEGAL** class. The truck must be presented at the pull in the same manner that is required for annual state inspection. **NO EXEPTIONS.** This means as stated in general rules, all of the factory original intended panels etc. must be in place. This includes but is not limited to; all lights in original position (i.e. headlights, tail lights...) Doors, hoods, fenders, grills, windshield etc... . Again, if you cannot pass annual inspection without an item, you cannot pull without that item. If any part of this is not clear or you are unsure please see track personnel **before** the pull starts.

**May NOT pull in any other class unless announced the day of the pull.** This is a non-points class. **\*\*Truck may be trailered in!**

**Engine Specs:**

- 1) 6 and 8 cylinders permitted.
- 2) Single turbo charger only – 2.6” inlet maximum on turbo.
- 3) Twin turbos stock only on 2008 or newer – factory equipped.
- 4) No nitrous oxide, water, propane, or methanol injection permitted.
- 5) Portable tuners (bully dog, etc.) are allowed.
- 6) No aftermarket air charge coolers or fuel icing/cooling allowed
- 7) Laptop computers are **not allowed.**
- 8) Must not smoke excessively.
- 9) Aftermarket exhaust ok.

**Other Specs:**

- 1) Suspension must have 1 inch minimum travel. No air shocks, air bags, or coil over shocks.
- 2) Traction bars permitted.
- 3) No front mounted or exposed weight.
- 4) No weight in cab or under hood – all additional weight must be in truck bed and secured.
- 5) DOT approved tires only.
- 6) Duallies allowed.

**Hitch Specs:**

- 1) Hitch height must not exceed more than 26” high – must be a stock receiver – fixed hitch allowed – absolutely no trailer balls. Hitch insert must be solid (no tube type inserts).
- 2) **Minimum hitch hole size of 3” and must be easily accessible.** A hole smaller than 3” will not accept the hook on the sled.
- 3) **No more than 1 ½ inches from rear of hook point to terminal end of hitch.**

**Safety Specs:**

- 1) Must wear helmet and seatbelts.
- 2) Fire extinguisher recommended.
- 3) Mud flaps required.

**Also -All General Safety Rules Apply!**  
**Violation of any rule will be a disqualification for the event in which  
the violation occurs!**