

Northeast Sled Services LLC
2019 4x4 Enhanced Diesel / 8500lbs

General Diesel truck specifications explained:

May not pull in more than 2 classes unless announced the day of the pull.
May pull in 3.0 class, but not workstock class.

Engine Specs:

- 1) 6 and 8 cylinders permitted, must be from 1 ton or less vehicle.
- 2) Single turbo charger only – 2.6” inlet maximum on turbo.
- 3) Twin turbos stock only on 2008 or newer – factory mass equipped.
- 4) Non factory style air intake **before** turbo permitted.
- 5) No nitrous oxide, propane, or methanol injection permitted.
- 6) Water injection ok.
- 7) Air charge coolers allowed (ice, etc.)
- 8) Portable tuners (bully dog, etc.) are allowed.
- 9) Laptop computers are **not allowed**.

Other Specs:

- 1) May have solid rear suspension.
- 2) Traction bars permitted.
- 3) Overhung or exposed weight permitted.
- 4) No weight in cab, all weight must be secured.
- 5) DOT approved tires only.
- 6) Dual rear tires permitted.
- 7) Must have driveline shielding same as 3.0 class.
- 8) Must have steel flywheel and **SFI approved** steel bellhousing for manuals, or trans shield for automatics.

Hitch Specs:

- 1) Hitch height must not exceed more than 26” high at top of the hitch point – must be a stock receiver – fixed hitch allowed – absolutely no trailer balls. Hitch insert must be solid (no hollow tube type).
- 2) **Minimum hitch hole size of 3” and must be easily accessible.** A hole smaller than 3” will not accept the hook on the sled.
- 3) **No more than 1 ½ inches from rear of hook point to terminal end of hitch.**

Safety Specs:

- 1) Must wear helmet and seatbelts.
- 2) 2lb “ABC” dry chemical Fire extinguisher required.
- 3) Mud flaps required.
- 4) All other general rules apply.

Also -All General Safety Rules Apply!

**Violation of any rule will be a disqualification for the event in which
the violation occurs!**